

Tablet & Laptop Charging Cart

Type C



32 devices



48 devices



Ergonomic Handle

Comfortable ABS handle with rounded edges for easy and safe mobility



Security Lock

Dual-door structure with front and back locks



Cooling Fan Temperature Protection

Built-in fan with overload, short-circuit and leakage protection



Large Capacity

Industrial fireproof panels with ventilation and heat dissipation
Supports centralized charging and management



Universal Casters (3-inch)

Silent casters with brakes smooth-rolling, and reinforced anti-collision corners

TDS-32C | TDS-48C Mobile Charging Cart Specifications

Model	TDS-32C	TDS-48C
Device Capacity	32 devices	48 devices
Dimensions	58.2 (W) × 41.5 (D) × 74.7 (H) cm (incl. wheels)	58.2 (W) × 41.5 (D) × 101.6 (H) cm (incl. wheels)
Compartment Size	2.5 (W) × 38 (D) × 24 (H) cm (each slot)	2.5 (W) × 38 (D) × 24 (H) cm (each slot)
Weight	35.2KG	51KG
Rows	2 Rows	3 Rows
Frame Material	1.5 mm steel panels + ABS partitions	
Frame Structure	Left-right welded frame with reinforced partitions	
Lock	Mechanical lock	
Casters	4 casters (Front 2 with brakes)	
Input Voltage	110V-240V	
Input Frequency	50/60HZ	
Power Output	1100W / 1650W	
Rated Current	15 A	
Cooling System	Auto reset at 35±8°C	
Dielectric Strength	Withstood voltage: 2000V AC / 10mA / 1 min	
Leakage Protection	1 pc, <1.0 mA (Vin = 110 Vac)	
Cooling Fans	2 pcs	
Main Power Management	Main Power Switch	

* Design and specifications are subjected to change without prior notice

